

# Energy Product Key

PRODUCT KEY								
Conductor	<b>Cu</b> Copper	<b>Al</b> Aluminum						
Strand	<b>Solid</b> Solid	<b>B</b> Class B	<b>Filled B</b> Filled Class B					
Voltage	<b>300V</b> 300 Volts	<b>600V</b> 600 Volts	<b>MV</b> 5kV—35kV	<b>2kV</b> 2000 Volts				
Insulation	<b>PVC</b> Polyvinyl Chloride	<b>PVC Nylon</b> Polyvinyl Chloride covered with Nylon	<b>PE PVC</b> Polyethylene covered with Polyvinyl Chloride	<b>EPR</b> Ethylene Propylene Rubber	<b>XLPE</b> Cross-linked Polyethylene	<b>TR XLPE</b> Tree-Retardant Cross-linked Polyethylene		
Shield/Neutral	<b>IS Alum Mylar</b> Individually Shielded Aluminum/Mylar	<b>OS Alum Mylar</b> Overall Shielded Aluminum/Mylar	<b>IS Alum Mylar OS</b> Individually and Overall Shielded Aluminum/Mylar	<b>OS Copper Tape</b> Overall Shielded Copper Tape	<b>Copper Tape</b> Copper Tape	<b>NONE</b> No Shield	<b>RCN</b> Reduced Concentric Neutral	<b>FCN</b> Full Concentric Neutral
Armor	<b>AIA</b> Aluminum Interlock Armored	<b>TECK</b> Teck Built						
Jacket	<b>PVC</b> Black Polyvinyl Chloride	<b>LLDPE</b> Linear Low-Density Polyethylene	<b>CPE</b> Chlorinated Polyethylene					